



802.11ac 2.4GHz

300Mbps

802.11ac 5GHz

900Mbps





RC412

1GE WAN+3GE LAN AC1200 DualBand Router



IPv4 & IPv6 Dual stack



Parents Control



RT069



MESH

Introduction

RC412 is 1GE WAN+3GE LAN AC1200 WiFi Router.It's design integration extremely high, not only making the device smaller and lighter in size, but also achieving lower power consumption and more green and energy-saving. The RC412 is equipped with 4*5dBi external antennas, providing stable network connectivity while ensuring signal coverage. In addition, RC412 also supports Mesh networking technology, achieving full WiFi coverage and seamless roaming, bringing users an excellent network experience.

It delivers the speed and reliability needed for applications such as lag-free multiple HD video streaming, multi-player gaming, ultra-fast speed and a secure and reliable connection to the Internet. It is compatible with next generation WiFi devices and backward compatible with previous generation WiFi devices. It enables HD streaming throughout your home. With up to 300+900 Mbps speed and simultaneous dual band WiFi technology, it avoids wireless interference, ensuring top WiFi speeds and reliable connections. These technologies also provide ultimate connectivity for the latest dual band mobile devices like iPads and iPhones.

Product Parameters

| Hardware Parameter | |
|---------------------|---|
| Dimension | 185mm×114mm×30mm (L×W×H) |
| Net weight | 180g |
| Operating condition | Operating temperature: -10 ~ +40°C Operating humidity: 10 ~ 90% (non-condensing) |
| Storing condition | Storage temperature: -40 ~ +70°C Storage humidity: 5 ~ 95% (non-condensing) |
| Power adapter | DC 12V/1.0A, external AC-DC power adapter |
| Interfaces | 1×GE WAN+3×GE LAN+WiFi AC1200 |
| Buttons | Reset,WPS/Mesh |
| Indicators | SYS |

| Interface Parameter | |
|---------------------|---|
| WAN/LAN interface | • 4×GE Auto-negotiation RJ45 ports,1×GE WAN + 3×GE LAN |
| WiFi interface | Compliant with IEEE802.11b/g/n/ac WiFi: 2.4GHz 2×2, 5.8GHz 2×2 MIMO 4*5dBi external antennas Multiple SSID |



| Software Features | |
|-----------------------|---|
| Layer3 | IPv4, IPv6 and IPv4/IPv6 dual stack Support bridge, router & bridge/router mixed mode DHCP v4/v6 Client/Server, PPPoE & Static Support Static Routing Support Hardware NAT |
| Multicast | Support IGMP v2 and MLD proxy/ snooping Support MultiCast VLAN & MultiCast Maximum Address |
| Security and Firewall | DDoS, Filtering Based on ACL/ MAC/ URL Support DDNS, ALG, UPnP, Port forwarding, DMZ HTTP/ SSH/ Telnet Service Access Control Support Parent control Support PPTP, L2TP, Pass-through service |
| QoS | Support 4 queuesSupport SP, WRR, 802.1P and DSCP |
| WiFi | Wi-Fi 6: 802.11a/n/ac/ax 5GHz & 802.11g/b/n/ax 2.4GHz WiFi Encryption:WEP-64/WEP-128/ WPA/WPA2/WPA3 Support WiFi Easy-mesh function Support MU-MIMO & OFDMA Support QoS Support WMM Support BSS-Coloring&Beamforming&Beamsteering |
| Management | Support Telnet, CLI ,TR069 and Web management |

Package

| Package | • 1 x Router |
|---------|--------------------------------|
| | • 1 x Quick Installation Guide |
| | • 1 x Power Adapter |

Ordering information

| Product Name | Product Description | Accessories |
|--------------|------------------------------------|---------------------------------|
| RC412 | 1GE WAN+3GE LAN+AC1200 WiFi Router | AC-DC power adapter: DC12V/1.0A |