



802.11ax 2.4GHz

574Mbps

802.11ax 5GHz

2402Mbps





RX430

WiFi 6 4GE AX3000 DualBand Router



IPv4 & IPv6 Dual stack



Parents Control



WAN/LAN Port Adaptive



MESH

Introduction

RX430 is 4GE AX3000 WiFi Router.It's design integration extremely high, not only making the device smaller and lighter in size, but also achieving lower power consumption and more green and energy-saving. Equipped with WAN/LAN Port adaptive function, it enhances the flexibility of port usage. The RX430 is equipped with 4*5dBi external antennas, providing stable network connectivity while ensuring signal coverage. In addition, RX430 also supports Mesh networking technology, achieving full WiFi coverage and seamless roaming, bringing users an excellent network experience.

It delivers the speed and reliability needed for applications such as lag-free multiple HD video streaming, multi-player gaming, ultra-fast speed and a secure and reliable connection to the Internet. It is compatible with next generation WiFi devices and backward compatible with previous generation WiFi devices. It enables HD streaming throughout your home. With up to 574+2402 Mbps speed and simultaneous dual band WiFi technology, it avoids wireless interference, ensuring top WiFi speeds and reliable connections. These technologies also provide ultimate connectivity for the latest dual band mobile devices like iPads and iPhones.

Product Parameters

Hardware Parameter	
Dimension	185mm×114mm×30mm (L×W×H)
Net weight	180g
Operating condition	 Operating temperature: -10 ~ +40°C Operating humidity: 10 ~ 90% (non-condensing)
Storing condition	 Storage temperature: -40 ~ +70°C Storage humidity: 5 ~ 95% (non-condensing)
Power adapter	DC 12V/1.0A, external AC-DC power adapter
Interfaces	1×GE WAN+3×GE LAN+WiFi AX3000
Buttons	Reset,WPS/Mesh
Indicators	SYS

Interface Parameter	
WAN/LAN interface	 4×GE Auto-negotiation RJ45 ports,1×GE WAN + 3×GE LAN WAN/LAN Port Adaptive
WiFi interface	 Compliant with IEEE802.11b/g/n/ac/ax WiFi: 2.4GHz 2×2, 5.8GHz 2×2 MIMO 4*5dBi external antennas Multiple SSID



Software Features	
Layer3	 IPv4, IPv6 and IPv4/IPv6 dual stack Support bridge, router & bridge/router mixed mode DHCP v4/v6 Client/Server, PPPoE & Static Support Static Routing Support Hardware NAT
Multicast	 Support IGMP v2 and MLD proxy/ snooping Support MultiCast VLAN & MultiCast Maximum Address
Security and Firewall	 DDoS, Filtering Based on ACL/ MAC/ URL Support DDNS, ALG, UPnP, Port forwarding, DMZ HTTP/ SSH/ Telnet Service Access Control Support Parent control Support PPTP, L2TP, Pass-through service
QoS	Support 4 queuesSupport SP, WRR, 802.1P and DSCP
WiFi	 Wi-Fi 6: 802.11a/n/ac/ax 5GHz & 802.11g/b/n/ax 2.4GHz WiFi Encryption:WEP-64/WEP-128/ WPA/WPA2/WPA3 Support WiFi Easy-mesh function Support MU-MIMO & OFDMA Support QoS Support WMM Support BSS-Coloring&Beamforming&Beamsteering
Management	Support Telnet, CLI ,TR069 and Web management

Package

Package	• 1 x Router
	• 1 x Quick Installation Guide
	• 1 x Power Adapter

Ordering information

Product Name	Product Description	Accessories
RX430	1GE WAN+3GE LAN+AX3000 WiFi Router	AC-DC power adapter: DC12V/1.0A